

Date

Thursday, 2/23/2006 10:23:19 AM

User:

Kim Johnston

Process Sheet

Customer

: CU-DAR001 Dart Helicopters Services

Job Number **Estimate Number** : 25916

P.O. Number

: 10820 : NA

This Issue

: 2/23/2006

: NA : 24849

S.O. No. : NIA

Type

: MACHINED PARTS

Drawing Name

Part Number Drawing Number : D26661 D2666 REV. B

: SADDLE, INBOARD, LS, 206

Project Number Drawing Revision

: N/A

Material **Due Date**

: 3/22/2006

Qty:

Each 12 Um:

Written By

Prsht Rev.

First Issue

Previous Run

Checked & Approved By

Comment

: Est:

Removed P/O for Powder Coat - in house

processEC

Additional Product

Job Number:



Seq. #:

Machine Or Operation:

Description: 7075-T7351 2X6X6.25

1.0 D6101001



Comment: Qty.:

1.0000 Each(s)/Unit Total: 12.0000 Each(s)

7075-T7351 2X6X6.25 Issue material from stock: Cut Size 2.0 x 6.25 X 6.0 Grain Along Long 6.0 Length

2.0

HAAS1







Comment: HAAS CNC VERTICAL MACHINHYG #1

Program batch number. 1-Inspect part number and batch number are programmed correctly.

2-Fixturing W/O No. _____

3-Fixturing Inspection last completed on Section by

4-Machine Step No 1 of Folio and visually inspect as per attached Dimension Sheet 5-Machine Step No 2 of Folio and visually inspect as per attached Dimension Sheet

6-Machine Step No 3 of Folio and visually inspect as per attached Dimension Sheet

7- Deburr

CONVENTIONAL MILLING MACHINE

3.0

MILLING CONV





Comment: CONVENTIONAL MILLING MACHINE

Machine Keyway and inspect per attached dimension sheet

4.0

QC2

INSPECT PARTS AS THEY COME OFF MACHINE

b







Dart Aerospace Ltd

W/O:			WORK ORDER CH	ANGES	 				
DATE STEP		PROCEDUR	E CHANGE		Ву	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector
		, V	*	·			·		
			•	·		*			
			***			• \$			
Part No):	PAR #: Fau	It Category:	NO	R: Yes	Mo) DQ	A. LI	Date: Z	06/67/08

QA: N/C Closed: ____ Date: ____

NCR:			WORK ORDER NON-CONFORMANCE (NCR)								
		Description of NC		Corrective Action			Verification	Approval Chief Eng	A		
DATE	STEP	Section A	rescription of NC		tion Sign & Date		Section C		Approval QC Inspector		
		·									
		·									
	<u> </u>										

NOTE: Date & initial all entries

Thursday, 2/23/2006 10:23:19 AM Date: User: Kim Johnston **Process Sheet** Drawing Name: SADDLE, INBOARD, LS, 206 Customer: CU-DAR001 Dart Helicopters Services Job Number: 25916 Part Number: D26661 Job Number: Description: Seq. #: **Machine Or Operation:** SECOND CHECK QC8 5.0 Comment: SECOND CHECK HAND FINISHING RESOURCE #1 HAND FINISHING 6.0 Comment: HAND FINISHING RESOURCE #1 Acid etch and Alodine as per QSI 005 4.1 7.0 POWDER COATING POWDER COATING Comment: POWDER COATING Powder Coat White Gloss (Ref: 4.3.5.1) as per QSI 005 4.3 INSPECT POWDER COAT/CHEMICAL CONVERSION 8.0 QC3 Comment: INSPECT POWDER COAT PACKAGING RESOURCE #1 9.0 PACKAGING 1 Comment: PACKAGING RESOURCE #1 Identify and Stock Location:_ DOCUMENT CONTROL 10.0 Comment: DOCUMENT CONTROL Inspection Level 21 Job Completion

Dart Aerospace Ltd

W/O:		WORK ORDER CHANGES									
DATE	STEP	PROCEDURE CHANGE	By Date Qty Approval Chief Eng / Prod Mgr QC Inspector								
Part No):	PAR #: Fault Category:	NCR: Yes No DQA: Date:								

Part No:	PAR #:	_ Fault Category:	NCR: Yes No DQA:	Date:
			QA: N/C Closed:	Date:

NCR:			WORK ORI	DER NON-CONFO	FORMANCE (NCR)						
		Description of NC		Corrective Action			Verification				
DATE	STEP	Section A	Initial Chief Eng	Action Descript Chief Eng	ion	Sign & Date	Section C	Approval Chief Eng	Approval QC Inspector		
-											
							٠ .				
								•			
		·									
					ļ						

NOTE: Date & initial all entries

DART AEROSPACE LTD	Work Order:	25916
Description: 206 Saddle, Inboard, Left side	Part Number:	D2666-1
Inspection Dwg: D2666 Rev. B		Page 1 of 1

Inspect dimensions highlighted on inspection sheet drawing D2666 Rev. B and record below:

				Re	corded Act	ual Dimens	ions		
Dim	Min	Max	Go/No Go Gauge	1	2	3	4	Ву	Date
Α	0.100	0.140		- 127	-125	, 122	-122		
В	0.100	0.140		128	-125	.123	. 124		
С	0.100	0.140		122	-123_	123	.#å3		
D	0.210	0.230		.224	.215	26	-216		
Е	1.245	1.255		1.250	1-250	1.247	1.250		
F	1.245	1.255		1.250	1-250	1-248	1.250		
G	5.990	6.010		5.997	5.996	5-998	5,997	· _ ·	
Н	0.510	0.515		6.575	0.775	0.575	0.5/5		
1	1.674	1.684		1.679	1.679	1.678	0.5/5		
J	2.495	2.505		2.500	2.500	2499	2.500		
K	0.257	0.262	DT8683		7		1.//		
L	0.312	0.317	DT8686						
М	0.235	0.240		0.236	0-236	0.736	0.286		
N	0.100	0.140		1/20	.112	, 114	1.115		
0	0.540	0.560		. 549	.549	. 548	.548		
P	0.490	0.510		500	.500	.500	.501		
Q	3.609	3.619		3.6/2	3.613	3613	3.613		
R	2.470	2.510		2.495	2495	2.495	2.495		
S	0.240	0.270		,259	-223	253	253		
T	0.100	0.180		.145	145	1.145	.145		
Ü	0.313	0.318	DT8686	-115	.,,,,		+		
<u>v</u>	1.125	1.145	<u> </u>	1.135	1.130	1.137	1-138		
W	1.565	1.585	DT8695 A/B	1.135		177	177		
X	1.000	11000	210000,12						
Ŷ		44							
Z									6
AA									
AB					· · · · · · · · · · · · · · · · · · ·				
AC	 :						1		
AD		-							
AE						<u> </u>			
AF							† · · · · ·		
AG					<u> </u>				
AH						-			
7111	Acc	ept/Reje	ct			1			

Measured by: T-L	1 Es	Audited by	The
Date: Och 29	06/67/24	Date:	04/07/24
			**

Rev	Date	Change	Revised by	Approved
Α		New Issue	RF	
В	99.04.19	Incorporated DSI 9095, DSI 9102 & DSI 9122 Rev. A	RF	
С	99.11.10	Added Dim. R-T	RF	
D	02.12.12	Reformat; Added Dim. U-W & DT8683, DT8686 & DT8695 A/B	KJ/RF	

DART AEROSPACE LTD	Work Order:	25916
Description: 206 Saddle, Inboard, Left side	Part Number:	D2666-1
Inspection Dwg: D2666 Rev. B		Page 1 of 1

Inspect dimensions highlighted on inspection sheet drawing D2666 Rev. B and record below:

·		,		Re	corded Act	ual Dimensi	ions		
Dim	Min	Max	Go/No Go Gauge	1	2	3	4	Ву	Date
Α	0.100	0.140		122	. 123	- 124,	124		
В	0.100	0.140		-123	124	1.124	L-123°_		
С	0.100	0.140		-124	121	125	125		
D	0.210	0.230		.218	.216	:219	-219		
E	1.245	1.255		1.250	1-249	1.250	1.250		
F	1.245	1.255		1.250	1.250	1-249	1.250		
G	5.990	6.010		5.997	5,997	5.997	5.996		
Н	0.510	0.515	,	0.515	0.515	0-5/5	0515		
Ī	1.674	1.684		1.679	1.679	1.678	1649		
J	2.495	2.505	•	2.499	2.500	2.499	2.500		
K	0.257	0.262	DT8683			//	1	*	
L	0.312	0.317	DT8686						
Μ.	0.235	0.240		0.236	0.236	0.236	5.236		
N	0.100	0.140		-115	.1/3	.1/4	-115		
0	0.540	0.560		.550	.549	.550	.550		
Р	0.490	0.510		. 200	.500	.501	- 500		
· Q	3.609	3.619		13.6/4	3.613	3.6/3	3.613		
R	2.470	2.510		2,495	2.495	2.495	2.495		
S	0.240	0.270		.254	-255	,256	-224		
T	0.100	0.180	•	-145	.145	.145	-145		
U	0.313	0.318	DT8686			/ /			
V	1.125	1.145		1.134	1./31	1.135	1.135		
W	1.565	1.585	DT8695 A/B		/ '				
Χ									
Υ									
Z									
·AA									
AB									
AC									
AD.									
AE									·
AF									
AG									
AH			~						
	Acc	ept/Reje	ct	<u></u>					

Measured by: 51 / E Audited by Date: Date: 0.4/07/3/4				
Date: 0/ /0//08 / -1/07/23/ Date: 0//07/3//	Measured by: 3	120	Audited by	_ m/
Date. $O(c/O(d\lambda^2))$ = $O(c/O+1)$ = $O(c/O+$		06/07/24	Date:	06/07/24

Rev	Date	Change	Revised by	Approved
Α		New Issue	RF	
В	99.04.19	Incorporated DSI 9095, DSI 9102 & DSI 9122 Rev. A	RF	÷
, C	99.11.10	Added Dim. R-T	RF	
· D	02.12.12	Reformat; Added Dim. U-W & DT8683, DT8686 & DT8695 A/B	KJ/RF	

DART AEROSPACE LTD	Work Order:	25916
Description: 206 Saddle, Inboard, Left side	Part Number:	D2666-1
Inspection Dwg: D2666 Rev. B		Page 1 of 1

Inspect dimensions highlighted on inspection sheet drawing D2666 Rev. B and record below:

				Recorded Actual Dimensions					
Dim	Min	Max	Go/No Go Gauge	1	2	3	4	Ву	Date
Α	0.100	0.140		. /24	122	- 122	-125		
В	0.100	, 0.140		.123	-122_	123	125		
С	0.100	0.140		.125	.123_	1/25	.125		
D	0.210	0.230		1.217	-216	.219	- 220		
E	1.245	1.255		1,250	1.250	1.249	1.251		
F	1.245	1.255		1.250	1.250	1-250	1.250		
G	5.990	6.010		5.998	5.998	5-997	.5998		
H	0.510	0.515		0.515	0-515	0:565	1.679	ļ	
	1.674	1.684		1-679	1.679	1.649			
J	2.495	2.505		3,499	2-498	2.500	2.500		······
K	0.257	0.262	DT8683	7	//	1			
L	0.312	0.317	DT8686						*
M	0.235	0.240	,	0.237	0-237	0.238	0.237		
N	0.100	0.140		. 117	.119	~11.8 @·538	- 120		
0	0.540	0.560		-550	.550	. 549	. 549		•
Р	0.490	0.510		.500	-499	. 200	,501		
Q	3.609	3.619		3.614	3-613	3.613	3.613		
R	2.470	2.510	•	2.495	2.495	2.495	2.495		
S	0.240	0.270	,	, 252	-252	-823	.2SO		
Т	0.100	0.180		.145	-145	.145	-145		
U	0.313	0.318	DT8686						
V	1.125	1.145		1/35	1./36	1.137	7./37		
W,	1.565	1.585	DT8695 A/B						
X									
Y									
Z			,						
AA									
AB		• -							
AC									
AD.									<u>-</u>
AE'									
AF									
AG									
AH								·	
Accept/Reject						<u></u>			

*		· ·	
Measured by: ろし	100	Audited by	me
Date: 06/0	16/30 / oblo7/24	Date:	06/07/24

Rev	Date	Change	Revised by	Approved
Α		New Issue	RF	
В	99.04.19	Incorporated DSI 9095, DSI 9102 & DSI 9122 Rev. A	RF	
С	99.11.10	Added Dim. R-T	RF	
. D	02.12.12	Reformat; Added Dim. U-W & DT8683, DT8686 & DT8695 A/B	KJ/RF	





"0.050 x 45" CHAMFER (TYP)

0.110

0.063

DESIGN DRAWN BY		DRAWN BY	DART AEROSPACE USA, INC.				
CHEC	KED	APPROVED	DRAWING NO.	REV. B			
	MW	18	D2666	SHEET 1 OF 1			
DATE	<u> </u>	1	MLE	SCALE			
97.0	07.11		SADDLE FWD INSIDE HIGH	2:5			
Α		97.03.25	NEW ISSUE				
		07.07.11	ANOTE AND MOTES ADDED				

R1.245

R1.135

EFFECTIVE DEOs 9095 9122 17/11/06 DS 98112/14 910Z 98/05/04

B 97.07.11 | ANGLE AND NOTES ADDED

R1.575 R1.685 1.000 120 0.500 0.110 0.225 1.615

- 0.250 SECTION A-A R0.50 0.625 1.807 1.808 0.550 1.679 1.362 0 R0.375 (TYP) 2.500 GRAIN 0.797 0.438 ENGRAVE PART Ø0.257 NUMBER AND 0 BATCH NUMBER TO MAX DEPTH ¢0.313 0.922 OF 0.010 WITH R0.50 MIN RADIUS R0.250 OF 0.010 R0.525 Ø0.312

RELEASE 0.050 x 45" CHAMFER

EXN 008

CPODIOSAS

MATERIAL: 7075 T651 OR 7075-T7351 (QQ-A-250/12) ACID ETCH, ALODINE PER DART QSI 005 4.1 FINISH:

PRIME, PAINT (EXCEPT BORES) PER DART QSI 005 4.2

0.500 -

NOTE:

ALL AROUND

D2666-1 SHOWN (D2666-2 IS OPPOSITE) BREAK ALL SHARP EDGES 0.010 TO 0.020 SHOP COPY TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTEDURN TO

1.250

6.000

ENGINEERING

1.250

Copyright 1997 by DART AEROSPACE USA, INC

UNCONTROLLED COPY SUBJECT TO AMENDMENT WITHOUT NOTICE · WORK ORDER NO. 259

1.60 a